


Fig. 1A

BEST AVAILABLE COPY






Fig 2A

Specifications	Option A	Option B
Hydrogen Storage	40 kg	80 kg
Storage Method	2 TriPacs™ (1,500 L)	4 TriPacs™ (3,000 L)
Overall Length	15 feet	17 feet
Curb Weight of HyHauler™	4,000 lbs.	5,500 lbs.
Power Requirement (US Grid)	10 kW (208 V, 3 Phase, 30 A or 240 V, 1 Phase, 50 A)	10 kW (208 V, 3 Phase, 30 A or 240 V, 1 Phase, 50 A)
Number of vehicles consecutively filled at 2 kg/vehicle (5,000 psi)	10-11	25-26
Number of vehicles consecutively filled at 5 kg/vehicle (5,000 psi)	3-4	9-10
Number of vehicles consecutively filled at 3 kg/vehicle (10,000 psi)	5-6	15-16
Time to recharge HyHauler™*	20 kg in 2-15 hrs.	40 kg in 3-24 hrs.

* Depending on source pressure and method of fill (i.e., cascade vs. compression only)

Fig. 2B




Fig. 3A

Number of Tubes	10-Tube
Hydrogen capacity	137,580 scf (717 lb)
Height	10 ft. 6 in.
Chassis & Tube Weight (3AAX)	60,000 lbs.
Overall Length	44 ft. 0 in.
Overall Width	8 ft. 0 in.
Chassis Weight	10,000 lbs.
Tube Diameter	22 in.
Tube Length (3AAX)	36 ft. 0 in.
Tube Specification	DOT 3AAX-2400
Avg. Tube Weight (3AAX)	5,000 lbs. Heavy Wall
Tube Nominal Water Volume (3AAX)	81.6 cf Heavy Wall
Avg. Operating Pressure (3AAX)	2,706 psig Heavy Wall

Fig 3B




Fig. 4




Fig. 5A

10/543123

Specifications	Option C	Option D
Hydrogen Storage	40 kg	80 kg
Storage Method	2 TriPacs™	4 TriPacs™
Overall Length	16 feet	20 feet
Curb Weight of HyHauler Plus™	7,000 lbs.	9,200 lbs.
Power Requirement (US Grid)	10 kW compressor, 50 kW electrolyzer (480 V, 3 Phase, 80 kVA)	10 kW compressor, 50 kW electrolyzer (480 V, 3 Phase, 80 kVA)
Number of vehicles consecutively filled at 2 kg/vehicle (5,000 psi)	10-11	25-26
Number of vehicles consecutively filled at 5 kg/vehicle (5,000 psi)	3-4	9-10
Number of vehicles consecutively filled at 3 kg/vehicle (10,000 psi)	5-6	15-16
On-board H ₂ production rate	1 kg/hr.	1 kg/hr.
Temperature Range (Electrolyzer)	36 to 104°F	36 to 104°F

Fig 5B




Fig. 6

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.